

## ***Automatic Small Stick Solid Drink Powder Packing Machine HY-YF50***



### **Features**

1. Adopt high configuration: Siemens PLC controller and color touch screen operation; Taiwan AIRTAC cylinder; France Schneider switching power supply, etc.
2. Servo heat sealing pull bag, smooth board side seal, vertical seal service, bag type exquisite.
3. Material: The contact part of the box and material is made of SUS304, which is in line with GMP production.
4. The heat-generating parts and moving parts are hidden in the protective cover, which is safe and reliable.
5. The equipment is equipped with casters for easy handling and movement.

### **Characteristics:**

1. Rounded shaped sachet, can design the size of the nozzle, tear horizontally to prevent the material from spilling; the arc corner can also prevent children from scratching, eye corners, increasing product safety.
2. If there are many kinds of materials, two sets of screws can be used. The ultra-fine powder adopts a long screw straight into the bottom of the bag, and the powder with little dust can be used. Through the short screw metering, the material is shaken up and down into the bottom of the bag through the forming tube, and the dust can be installed with a dust suction device;
3. The punching die adopts HKS-9 material. After six processing techniques, it has high durability and long service life.
4. A disinfection lamp is installed at the film pulling film to perform preliminary disinfection on the film.

5. Auxiliary equipment: loading machine + coding machine + finished product conveyor + vacuum cleaner.

**Specification:**

<b>Model</b>	<b>HY-YF50</b>
Filling Range	1-50ml
Sachet Size	W: 25-100mm, L: 30-180mm
Max. Film Width	220mm
Sachet Type	Rounded back seal, easy to tear.
Filling Method	Auger
Capacity	20-35 ppm
Power Voltage and consumption	220V50-60HZ/3KW
Air Pressure and Consumption	0.3m <sup>3</sup> /min 0.6-0.8Mpa
Dimension (L*W*H)	930*1500*2400mm
Weight	400KG
Packaging Film Materials	PE laminated film, such as PET/AL/PE, PET/PE, Nylon/PE, etc.
	Thickness: 0.08~0.12mm (3 or 4 layers)
	Inner core diameter: 75mm
	Outer roll diameter: 300mm-500mm