

Horizontal Flow Packing Machine DXD-300



DXD-300 Flow Packing Machine is suitable for pillow type packing of products such as, cakes, bread, chocolates, masks, plastic spoons and so on.

Technical Specification

- 1. Have painted cover, PC controller and stainless steel 304 for your choice according to needs of different customers
- 2. Thickened material, heavier machine, helps this flow wrapper runs faster and more stable.
- 3. Use of famous brand of electrical parts, ensures quality of this flow packing machine.
- 4. This packing machine is equipped with 3 servo motors, which ensures stable working and easier maintaining.

Technical Parameters

Max.Production Capacity Packing shape		最大生产能力 包装物形		40-200(单刀Single Cutter)	80-400(双刀Double Cutters)	200-400 (≡刀Three Cutters)
				方形、长方形、圆形、椭圆形、	片状等。Square, rectangle, circular,	, ellipse and flake etc.
Packing Range	Length of bag	包裝范围	袋长	170-1000mm	80-500mm	50-135mm
	Width		意度	35-100mm	35-100mm	60-100mm
	Height		高度	<60mm	<40mm	<30mm
Max.Dia.of Film		包装機最大直径		350mm	350mm	350mm
Max.Width of Film		包装膜最大宽度		300mm	300mm	300mm
Gross Power		总功率		4.5kW	4.5kW	4.5kW
Power Supply		电源		220V 50Hz	220V 50Hz	220V 50Hz
Gross Weight		总重量		900kg	900kg	900kg
Overall Dimension		外形尺寸		4300×850×1550mm	4300×850×1550mm	4300×850×1550mm
Packing Material		包装材料		OPP、CPP、PET镀铝膜、铝塑膜、纸塑、纸胶等单层多层等可热封材料		
				建议使用外层PET厚度0.013mm,内层CPP厚度0.023~0.027mm,复合低温膜		
			OPP, CPP, PET Metallized film, Al-plastic film, Paper-rubber complex			

Suggest to used wrapping film with material of PET13/CPP23-27