



Sugar Packing Machine TT-380



Application

1. The whole body 304 stainless steel high-precision structure, rust, and durable, easy operation and maintenance.
2. PLC, touch screen, stepper motor control, bag length set convenient and accurate.
3. Frequency control, bag more convenient and smooth, simple and quick, save time and film.
4. High sensitivity photoelectric eye color mark tracking, digital input sealing, and cutting position, so that the sealing and cutting positions are more accurate.
5. Temperature-independent PID control, better adapt to a variety of packaging materials.
6. From filling, bagging, printing date, inflatable (exhaust) one-time completion.
7. Drive system is simple, more reliable, and more convenient for maintenance.
8. All controls are implemented by software to facilitate functional adjustment and technology upgrades, never lagging behind.

Technical Parameters

Model	TT-380
Film width	max 320mm
Bag length	max 220mm
Bag width	50-150mm
Packaging Rate	5-60bags/min
Measurement Range	50-500ml
Film Thickness	0.04-0.08mm
Power	220V 50/60Hz 2KW
Machine Size	970*680*1950
Machine Quality	About 300KG
Optional device	Date coder, Hole punching device (Pinhole, Round hole, butterfly hole), Linking bag control device, Airfilling device, and Air exhaust device. Tear notch device, Nitrogen inflation device, Gusset bag