

## *Tray Less Biscuit Horizontal Flow Wrapper Packaging Machine ZP-500W*



### **Product advantages**

- 1) With menu storage and memory functions, the controller can save multiple sets of parameter configurations. When the product or packaging film is replaced, the formula can be used on the touch screen.
- 2) The horizontal flow wrapper packaging machine has advanced electronic anti-cutting and electronic anti-aircraft bag algorithms. The empty material film stops, saving packaging materials.
- 3) Horizontal flow wrapper packaging machine is controlled by independent servo motors, with a simple mechanical structure, stable operation, and low noise.
- 4) Automatically track the production feeding speed, and the horizontal flow packaging machine automatically accelerates and decelerates. High speed, high precision, speed up to 120 packs/min.
- 5) Man-machine interface, convenient and fast parameter setting, automatic tracking of color code, automatic correction of cutting length. Digitally input the sealing and cutting position to make the sealing and cutting position more accurate.
- 6) The standard horizontal sealing cutter shaft center distance is 132, and the horizontal sealing center distance can be changed according to the actual size of the product.

## Technical Parameters

<b>Machine Model</b>	<b>Tray Less Biscuit Horizontal Flow Wrapper Packaging Machine ZP-500W</b>
Packing speed	35-120 bags/min
Packing material	Plastic film (OPP/CPP、PT/PE、KOP/CPP、ALU-FOIL)
Bag style	Pillow type/fat pouch (3-side presealed)
Bag size (L*W*H)	60-Infinite mm, 30-150 mm, 30-75 mm
Film width	965-400mm
Packing Dimension (L*W*H)	4600mm*960mm*1600mm
Heat power	3.8kw
Motor power	2.5kw
Total power	6.3kw
Overall weight	820kg