

Yogurt Filling Machine



It uses the piston cylinder to fill the material in the glass. It can be used in food, chemical industry, medicine, cosmetics, pesticides and other industries. It can be used for filling liquids, especially high viscosity materials and foaming liquids, such as yogurt, soy sauce, jam, soy sauce, ketchup, honey, butter, lubricating oil, etc. It uses PLC control. It fixes the discharge port according to the filling cup, and the rest of operations can be completed on the touch screen. It not only has the common characteristics of automatic piston filling machine, but also expands the range of filling materials. Just as the filler material contains particles, solid strips can also be very useful fillers.

Six Competitive Edges of Our Yogurt Filling Machine:

- 1. We provide high-quality after-sales service.
- 2. It can be used with standard conveyor belt or pucks for unstable cups.
- 3. Design flexible.
- 4. Format size conversion is very fast and easy
- 5. We can connect you with the model of the gas station.
- 6. The filling nozzle is drip proof.

Communication:

- 1. We will prepare various information and introduce you to videos, pictures and how the machine works.
- 2. To ensure that we provide you with the right machines and solutions, we may ask you a lot about your needs.
- 3. We will give you samples to confirm the machine and production before we produce the machine.

- 4. We will test your machine with your real products, debug the machine until you are satisfied with the machine, and solve various problems of the machine.
- 5. We will help you in shipment and customs clearance and arrange affordable and safe shipping agents.

Shipment and trade terms:

We can do EXW, FOB, CNF, CIF, DDP. It also includes door-to-door, but you can trust us. We won't earn any fees in the freight

Express:

- 1. If we have a store, we can express the required spare parts by DHL on the day we receive your email, if out of stock, we will check the production date and reply to you on the day we receive your email.
- 2. If the parts of the machine are damaged during operation or transportation during the warranty period, DHL fee will not be paid.

Adjustment and inspection:

- 1. Your inspection agent or production personnel come to our site to inspect the machine.
- 2. We will make all modifications from the customer (which is feasible for our machine)
- 3. We suggested that you can give the real packaging and materials of the test machine to us.
- 4. We will run the whole machine for free and try our best to manufacture the products that customers really need, so as to make customers satisfied and assured.

Installation and after sale service:

- 1. We will send professional technicians to your company to install machines and train. Please prepare a Chinese translation.
- 2. For better installation and training. We can also bring your contractor to the company
- 3. In order to install the machine and operate the video, we will send you the machine manual with electrical drawings to introduce you to the machine components.
- 4. When the customer has trouble on the machine, please be sure to shoot a video to let us clearly see the problem. We will also solve every problem of customers through video and pictures.

Technical Parameters

	T
Diameter	1100*1100*1600mm
Weight	350KGS
Power	2 KW
Voltage	110V/ 60Hz 1P
Air pressure	0.6-0.8Mpa
Capacity	600-800 pcs/hour
Air consumption	0.6m³/min
Heating type	electrical heated
Working position	6
Machine frame	SUS 304