

Shrink Film Packaging Machine AS-350, DS-400, DS-500, DS-500E



There are 4 type of heat tunnel to run any kind of shrink material; they are heat tunnel for wrapping purpose, steam tunnel, heat tunnel for shrink sleeve & mini-type heat tunnel. Those heat tunnels are designed to conveyor speed controllable, compact dimension, power saving, quick shrinking, quick movable & saving space to reduce packaging cost. It can also work in line to connect upstream & downstream equipment to be fully automatic.

Features:

AS-350 & DS series can work with shrink material of PVC, POF, OPS, PET & OPSL for varied packages.

Specification:

AS-350

- Power: 1Ø 220V / 3Ø 220V
- Machine Dimension: 1800 x 730 x 1365 (m/m)
- Tunnel Dimension: 1000 x 350 x 150 (m/m)
- Heater: 7.2 (KW)
- Temp. in Tunnel: 200 (°C)
- Motor: AC1/4HP x 2
- Conveyor Speed: 0 - 30 (M/Min)
- Option: Standard Type

DS-400

- Power: 1Ø 220V / 3Ø 220V
- Machine Dimension: 1500 x 630 x 1560 (m/m)
- Tunnel Dimension: 900 x 400 x 200 (m/m)
- Heater: 9 (KW)
- Temp. in Tunnel: 200 (°C)
- Motor: AC40W x 1, AC1/2HP x 1
- Conveyor Speed: 0 - 30 (M/Min)
- Option: Standard Type, CE Type

DS-500

- Power: 3Ø 220V
- Machine Dimension: 1800 x 630 x 1610 (m/m)
- Tunnel Dimension: 1100 x 500 x 250 (m/m)
- Heater: 9 (KW)
- Temp. in Tunnel: 200 (°C)
- Motor: AC1/2HP x 1, AC1/4HP x 1
- Conveyor Speed: 0 - 30 (M/Min)
- Option: Standard Type, CE Type

DS-500E

- Power: 3Ø 220V
- Machine Dimension: 2400 x 830 x 1610 (m/m)
- Tunnel Dimension: 1100 x 500 x 250 (m/m)
- Heater: 9 (KW)
- Temp. in Tunnel: 200 (°C)
- Motor: AC1/2HP x 1, AC1/4HP x 1, AC1/10HP x 1
- Conveyor Speed: 0 - 20 (M/Min)
- Option: Standard Type, CE Type

Applications:

DSE is applied for PE shrink film.