



APC-C120 Automatic Desiccant Inserting Machine



The machine equipped with human-computer interface and PLC control system providing easy access to all settings within the range of parameters

High shear knife edge, accurate and reliable avoid breakage of the desiccant bags. Easy operation, simple maintenance and stable operation. Positioning adopts pneumatic clamping mechanism to clamp bottles stably and accurately.

Features:

- The compatibility is strong, suitable for all kinds of specifications, all kinds of round, oval, square, flat, square bottles.
- Color standard, colorless standard disc packaged desiccant bags.
- Adopting put desiccant with design, avoid uneven bags transfer, ensure the accuracy of the bag length control.
- Desiccant bag put thick adaptive design, avoid the happening of torn bags in the process of transmission.
- Accurate and reliable durable knife edge, high shear don't cut broken desiccant bags.
- Have no bottle don't work, breakdown self-check, desiccant bags into the bottle and so on many monitoring alarm control functions, to ensure the continuity of the equipment operation and the accuracy of the desiccant bags into.
- Fully automatic operation, and the upper and lower from spreading, a process that intelligence coordination is good, the need of personnel, to save human.
- Photoelectric sensors from Taiwan production, stable and durable.

Technical Parameters:

Applicable bottle type: ___round, oval, square, flat square bottles

Desiccant bag: ___disk desiccant bag, size according to the bottle size

Production capacity: ___ 50~120 bottles per minute
Power supply: ___ AC220V 50Hz 0.5kw
Air pressure: ___ 0.4Mpa
Overall dimension: ___ 1150×800×1900mm
Weight: ___ 300kg