

HGPS-4535 Automatic L Type Sealer and Shrink Packing Machine



Feature:

1. Heat shrinking machine adopt the technology of hot air circulating, so as to adjust temperatures by the use of automatic temperature regulator and to save energy.
2. Widely used in the packing of following products: food, drink, medicine, hardware, wood product, cosmetics, printing, plastics and electronic component etc.
3. All the shrink packing products are not only elegant in look, but also cost-saving in production.
4. In the meantime, shrink packing is conducive to the preserve of the sealed products.

Technical Parameters:

| Item | Details | |
|------------------------|---|--|
| Heating System | Heat Preservation Layer | Made from high temperature resistant rock wool, low temperature when it working, reduce the heat loss. |
| | Temperature Control | Use Taiwan ANV temperature controller and imported thermal induction, temperature around 0-220°C. |
| Conveying System | Motor | American enterprise VTV motor, reducer casing. |
| | Speed Controller | American enterprise VTV motor, to make sure smoothly conveying. |
| Controlling System | Contactora | CHINT, China |
| | Intermediate Relay | IDEC, Japan |
| | Temperature Controller | ANV, Taiwan |
| | Emergency Switch | IDEC, Japan |
| Machine Body | Outer Board | Use normal carbon steel plate after bending, and surface coating processing. |
| | Inner Board | Use galvanized sheet hydraulic. |
| Wind Conveying System | Specially designed wind conveying system, the product is heated evenly, high power wind conveying motor, to make sure the shrinking chamber is heated evenly. | |
| Speed | 2000-3000 bag/hour | |
| Voltage/Power | 380V/50Hz 10KW | |
| Machine Size | L1300*W715*H1455mm | |
| Max. Sealing Size | L400*W320*H125mm | |
| Shrinking Chamber Size | L1000*W450*H250mm | |