



Automatic Cartoning machine ANTZ-100P



This machine is suitable for cardboard case packaging of bottles (round, square), cosmetic, food and so on. It consists of direction folding (1-4 folds) and feeding equipment, cardboard case forming and feeding, batch number printing, sealing of case tongues at both ends etc. The whole encasing process is finished automatically. It can be added hot-glue machine.

Features

1. International famous brand of electric components such for PLC touch screen, frequency inverters etc.
2. Adopt human-machine operation system.
3. Automatically displaying device for trouble, speed and finished products counting.
4. Automatic detection and rejection device for lacking of blisters/goods or leaflets.
5. Stability performance with lubricate setting and controlling.

Main Technical Parameters

Encasing speed	30-100box/min	
Box	Quality requirement	250-350g/m ²
	Dimension range (L x W x H)	(65-180)mm x (30-85)mm x (15-50)mm
Leaflet	Quality requirement	50-65g/m ²
	Unfolded leaflet specification	(80-300)mm x (70-210)mm
	Folded leaflet specification(1-4)	(70-210)mm x (20-40)mm
Compressed air	Working pressure	0.5-0.7mpa
	Air consumption	120-160L/min
Power supply	220v 50hz	
Motor power	0.75kw	
Machine dimension	2800 x 880 x 1800(mm)	
Machine weight	1200kg	