

Pillow Bag / Gusseted Bag Basic Packing Machine GH-B-series



Feature:

1. Famous brand PLC control, system, large touch screen, convenient to operate;
2. Advanced design, high precision and fast speed;
3. No film alarm, saving materials and no waste film;
4. Photocell tracking system for precise bag length and position of film



Option parts:

1. Multi-heads combination weigher
2. Multi-heads linear weigher
3. Volumetric cups device
4. Auger measuring and filling device
5. Liquid filling pump
6. Counting number vibration feeder

Parameter:

Model	GH320B	GH420B	GH520B
Capacity	30-50bags/min	30-45 bags/min	25-40 bags/min
Volume	Max.500ml	Max.1000ml	Max.2000ml
Film width	Max.320mm	Max.420mm	Max.520mm
Bag size	L:50-230MM	L:50-300MM	L:80-350MM
	W:50-150MM	W:60-200MM	W:100-250MM
Bag type	Pillow bag/Gusseted		
Cutting	1.Flat Cutting; 2. Zigzag cutting; 3. Continuous cutting;		
Control	PLC+Servo+Touch screen		
Air consumption	0.8 MPA 0.25M3/MIN	0.8 MPA 0.4M3/MIN	0.8 MPA 0.5M3/MIN
Power Supply	2KW,	2.2KW,	2.5KW,
	220V/380V, 50Hz	220V/380V, 50Hz	220V/380V, 50Hz
Dimension (mm)	1200*905*1300	1260*1015*1560	1650*1180*1790
Weight	300KG	450KG	650KG
Model	GH620B	GH730B	GH1050B
Capacity	20-40bags/min	15-35bags/min	15-30bags/min
Volume	Max.3000ml	Max.5000ml	Max.8000ml
Film width	Max.620mm	Max.730mm	Max.1050mm
Bag size	L:100-400M	L:100-450MM	L:300-800MM
	W:100-300MM	W:80-350MM	W:300-500MM
Bag type	Pillow bag/Gusseted		
Cutting	1.Flat Cutting; 2. Zigzag cutting; 3. Continuous cutting;		
Control	PLC+Servo+Touch screen		
Air consumption	0.8 MPA 0.6M3/MIN	0.8 MPA 0.7M3/MIN	0.8 MPA 0.8.0M3/MIN
Power Supply	4KW,	5KW,	5.5KW
	220V/380V, 50Hz	220V/380V, 50Hz	220V/380V, 50Hz
Dimension (mm)	1580*1120*1930	1705*1310*2190	2600*1830*2990
Weight	800KG	900KG	1100KG