



## ***DPP138C/250C AL/PL Blister Packing Machine***



### **Performance and Characteristics:**

Variable Frequency Speed Regulating, PC Circuit Control Panel.

Adjustable travel adopts manipulator grip equipped with inching device, which has accurate synchronization.

With cylinder heat-sealing, the upper and lower checkers ensure the effect of heat-sealing.

Mould spout location is convenient for replacing mould.

Waste Automatic Recovery Device.

DA vibrating disk feeder, which is suitable for feeding breakable pills and milk, pills with dust on surface.

### **Main Technical Specifications:**

Punching Frequency: 20-40 times/min

Punching Plate: 2-3 plates/time

4 plates/time (DPP250C)

Adjustable Scope of Travel: 30-120mm

Packing Efficiency: 4800-7200 plates/hour

4800-9600 plates/hour (DPP250C)

Max Forming Area and Depth: 140x110x18mm

245x112x30 mm (DPP250C)

Specifications of Packing Material:

Medical PVC: 150x0.25(0.15-0.5)mm

250x0.25(0.15-0.5)mm (DPP250C)

PTP: 150x0.02 mm

250x0.02 mm (DPP250C)

Air-compressor:  $\geq 0.15\text{m}^3/\text{min}$ ;  $0.22\text{m}^3/\text{min}$  (DPP250C)

Pressure: 0.5-0.7Mpa

Overall Size: 2200x750x1650mm

2800x800x1900 mm (DPP250C)

Weight: 1500kg; 1500kg (DPP250C)