

VFFS Full Fill Bagger VPZ52



Technical advantage

- 95% spare parts are made of stainless material, exposed electric equipment use IP65 waterproof standard, in a humid environment, still can stable-operation, and keep new for a long time.
- Adopted with a swing arm type fiber folder traction tension membrane (servo motor with planetary gear box), and has the function of automatic adjustment.
- The upper and lower adjustable film fupping adapt to the different length of bag, material and capacities.
- Material testing photocell can through the thin film material, can accurately give feedback information to full of packaging process.
- The eight unfolding wheel easily solve the four sides sealing bag easily overlapping problem.
- The hexagonal former design, molding bag better, a strong guarantee the appearance of the appearance of the bag.
- Horizontal sealing dynamic design have two optional device that cylinder power and servo fast transverse sealing.
- The vertical sealing structure using a new type of screw mandrel to adjust different specifications

Technical Parameters:

Model	CB-VPZ52
Packing speed	Max 30bags/min
Film width range	160mm-520mm
Bag size	(L)120-350mm(W)80-250mm
Bag type	Pillow bag
Film thickness	0.04-0.09mm
Air consumption	0.8Mps 0.5m ³ /min
Power supply	3.4KW 220V 50Hz/60Hz
Dimension	(L)1610*(W)1460(H)2340mm
Weight	560kg