

PZB-600W Automatic Flow Packing Machine



The PZB-600W automatic flow packaging machine is suitable for pillow packaging of biscuits, sandwich biscuits, wafer biscuits, cookies and other products without plastic trays. The machine adopts servo motor, PLC, sensor control, and touch screen display to ensure the smooth operation of the machine. The machine is equipped with an automatic ink wheel coding machine and a gusset system to ensure that the packaging effect of the bag is very beautiful. This machine can realize linkage production with cartoning machine, automatic inkjet printer and other equipment.

Performance characteristics

1. The servo motor is adopted, the control is more precise, the stepless speed control can be realized, and the operation process is dynamically adjusted.
2. The large color touch screen design can realize the storage and recall of packaging data, automatic adjustment, tracking, searching for cut points, alarm prompts, fault point prompts, packaging count accumulation, automatic display of pause bag length speed, and accurate cutting.
3. Photoelectric detection and two-way tracking can effectively eliminate packaging errors and avoid material waste.
4. The new type of longitudinal sealing heating can be sealed at low temperature, reducing the hot film when parking, and greatly reducing the rejection rate.
5. The operating mechanism of the whole machine is designed with an open cantilever structure and is driven by a synchronous belt. The structure is exquisite and easy to maintain and maintain. Greatly reduce the transmission noise and make the machine run more smoothly.
6. The special clip and transportation design ensures the good packaging effect of multiple rows of biscuits.
7. All food contact parts are made of 304 stainless steel.
8. The machine is equipped with a 4-meter-long conveying mechanism to facilitate manual loading of biscuits onto the conveying mechanism.

Technical Data:

Model	PZB-600W
Packing speed	20-70 Bags/minute
	The packaging speed depends on the packaging product material, size, packaging film, and feeding method.
Max packing film width	600mm
Packing film range	Length: 90-500mm
	Width: 35-180mm
	Height: 30-50mm, 50-80mm
Packing film	Suitable for heat-sealing packaging composite film, OPP/PP, PT/PE, AL/PE, etc.
Standard voltage requirements	Single-phase 220VAC, 50HZ,
	Customized according to customer's actual requirements.
Machine dimension	About 5500*1180*1750mm
Machine Weight	About 1350kg