

LQ-BTB-300A/LQ-BTB-350 Overwrapping Machine For Box



This machine is widely applicable to the automatic film packaging (with gold tear tape) of various single boxed articles. With new-type of double safeguard, no need to stop the machine, other spare parts will not be damaged when the machine runs out of step. Original unilateral hand swing device to prevent adverse shaking of the machine, And the non-rotation of the hand wheel when the machine keeps running to secure the security of the operator. No need to adjust the height of worktops on both sides of the machine when you need to replace moulds, no need to assemble or dismantle the material discharge chains and discharge hopper.

Feature

1. No need to regulate the height of two work tops of the machine when the mould need to be replaced, no need to assemble or dismantle the material discharge chains and discharge hopper. Reduce the replacement time of the mould four hours to the present 30 minutes.
2. New-type double safeguard mechanisms are used, hence other spare parts will not be damaged when the machine runs out of step without stop of the machine.
3. Original unilateral hand swing device to prevent the machine shaking adversely, and the non-rotation of the hand wheel during the running of the machine can secure the security of the operator.
4. New-type double-rotary film cutter can ensure no need to mill the blade during many-year use of the machine, which overcomes the defect that the traditional stationary single-rotary film cutting cutter was easily worn.

Technical Parameter

Model	LQ-BTB-300A	LQ-BTB-350
Packing Material	BOPP film and gold tear tape	BOPP film and gold tear tape
Packing Speed	40-70 packs/Min	30~60 packs/min
Max Packing Size	(L)240×(W)120×(H)60mm	(L)300×(W)120×(H)60mm
Electric Supply & Power	220V 50Hz 5kw	220V 50Hz 5kw
Weight	500kg	600kg
Overall Dimensions	2000×700×1400mm(L*W*H)	(L)2000×(W)800×(H)1400mm